

Power to Believe. Power to Act.



### The Powerheart® G5

# Empowering Rescuers at Every Level to Save Lives

Whether you are an experienced rescuer or a first-time responder, the Powerheart G5 automated external defibrillator (AED) provides a powerful combination of features that help rescuers provide sudden cardiac arrest (SCA) victims with swift, effective, and life-saving therapy. The Powerheart G5 is the first FDA-approved AED to combine fully automatic shock delivery, dual-language functionality, variable escalating energy, and fast shock times to help save an SCA victim's life.

#### Easy without compromise

Perform each step of the rescue with user-paced instruction from RescueCoach™ voice and text prompts. Pads can be placed on either side of a victim's chest, and the Powerheart G5 only provides an automatic shock when it is required. After the rescue, extract event data immediately from a USB port.

#### Reliable and rugged

Feel confident knowing your Powerheart G5 will be ready when called upon thanks to the highly visible Rescue Ready® indicator that communicates rescue status and confirms that the internal circuitry, medical-grade battery, and rescue pads have passed daily, weekly, and monthly self-tests. In fact, a collective 4,100 hours of Rescue Ready self-tests around the world are performed each day. The durable G5 has been tested to military standards and features an IP55 rating for protection against dust and water.



# Powerheart® G5 AED

| TECHNICAL SPECIFICATIONS             |  |
|--------------------------------------|--|
| DEFIBRILLATOR                        |  |
| Operations                           | Fully automatic and semi-automatic versions  |
| Waveform                             | STAR® biphasic truncated exponential   |
| Therapy range (J)                    | 95J to 354J (adult)  |
| Fast shock feature                   | Able to deliver a shock after the end of a CPR cycle in 10 seconds or less   |
| Voice prompts                        | RescueCoach™ prompts provide user-paced instruction  |
| Text screen                          | Displays rescue prompts and critical rescue information  |
| Audible alerts                       | Voice prompt, system alert   |
| Synchronized shock                   | Built-in automatic synchronization feature   |
| Pacemaker pulse detection            | Yes  |
| Pediatric capability                 | Therapy range (VE) 22J to 82J, pediatric prompts   |
| Dual language                        | Latin American Spanish or French Canadian (optional)*  |
| Customizable                         | Voice prompt, CPR settings, and shock protocols via AED Manager  |
| CPR                                  | Metronome for CPR compression rate   |
| Visible indicators                   | Rescue Ready®, battery, service, and pad status  |
| Warranty                             | 8 years  |
| PHYSICAL / ENVIRONMENTAL             |  |
| Dimensions (H $\times$ W $\times$ D) | $3.4 \text{ in} \times 9.0 \text{ in} \times 11.8 \text{ in} (9 \text{ cm} \times 23 \text{ cm} \times 30 \text{ cm})$ |
| Weight                               | 5.7 lbs (2.6 kg), including battery and pads   |
| Dust/water resistance                | IP55 (IEC 60529)   |
| Operating temperature                | 32 °F to +122 °F (0 °C to 50 °C)   |
| Altitude                             | -1,253 ft (-382 m) to (15,073 ft) 4,594 m  |
| Drop                                 | MIL-STD-810G, 516.6 (Procedure IV) for 1.22 m drop   |
| Shocks                               | MIL-STD-810G, 516.6 (Procedure 1)  |
| Vibration (sine and random)          | MIL-STD-810G, 514.6 (Procedure 1, Cat 24)  |
| EMI (radiated/immunity)              | IEC 60601-2-4  |
| PADS                                 | Intellisense™ Defibrallation Pads  |
| Туре                                 | Disposable, non-polarized (pads can be placed in either position)  |
| Shelf life                           | 2 years  |
| BATTERY                              | Intellisense® Lithium Battery  |
| Guarantee                            | 4-year, full operational replacement   |
| Capacity                             | 420 shocks (typical) at 300VE  |
| AUTOMATIC SELF-TESTS                 |  |
| Daily, weekly, and monthly           | Electrical circuitry, AED software, medical grade battery and defibrillation pads (presence and function)              |
| Weekly                               | Includes partial energy charge   |
| Monthly                              | Includes full energy charge cycle  |
| EVENT DOCUMENTATION                  | 00 minutes of rescue data multiple rescue functionality  |
| Internal memory                      | 90 minutes of rescue data, multiple rescue functionality   |
| ECG and rescue review                | Viewable via AED Manager reporting and configuration software  |
| Communications                       | USB cable or USB memory stick  |

<sup>\*</sup>Check for availability in your area.

## At the Heart of Saving Lives®

Cardiac Science Corporation • N7 W22025 Johnson Drive, Suite 100, Waukesha, WI 53186 USA +1.262.953.3500 • US toll-free +1.800.426.0337 • Fax: +1.262.953.3499

Orders and Customer Care \* +1.262.953.3500 \* US toll-free +1.800.426.0337 \* Fax: +1.262.798.8292 \* care@cardiacscience.com Technical Support \* (US) Fax: +1.262.798.5236 \* technical support @ cardiacscience.com \* (International) international service @ cardiacscience.com \* (International) \* (Inte



